

# Byok

## Assiale L



### Dimmbarkeit

- DALI dimmable
- Daylight and motion sensor

### Version

- rotatable
- fixed

## Technical details

<b>Country of Manufacture</b>	 Germany
<b>Manufacturer</b>	Byok
<b>Designer</b>	Kai Byok
<b>Protection class / IP rating</b>	IP20
<b>Contents of the package</b>	LED
<b>voltage suitability</b>	230 - 240 Volt
<b>material</b>	aluminum
<b>Power (max. Watt)</b>	60 Watt
<b>LED</b>	inclusive
<b>Colour Rendering Index</b>	80
<b>Color temperature in Kelvin</b>	3,000 warm white
<b>Total luminous flux in lm</b>	4,400 lm downlight, 4,400 lm uplight
<b>light distribution</b>	directly and indirectly
<b>Dimensions</b>	H 48 cm   B 7 cm   L 180 cm

## Description

The Byok Assiale L is attached directly to the ceiling. It is available as fixed and rotatable. The joint of the rotating lamp is both flexible and robust. A spring-loaded mechanism protects the joint when the lamp is rotated.

The light is offered in anodized aluminum as well as on request powdered in RAL colours. The lamp is offered in three versions: on site DALI dimmable or controllable with light and motion sensors. It emits up- and downlight. In contrast to the Assiale T, this lamp has an L-shape.