

# less'n'more

# **Ylux Pendant Light**

## Leuchtenkopf

- glossy white
- black matt
- matt white
- glossy black
- · polished aluminum

#### **Baldachin**

- concrete white
- concrete grey

#### Kabelfarbe

- red
- black
- white

#### Dimmbarkeit

- Rotary dimmer on head
- on site dimmable with a trailing edge dimmer

# Description

The Less'n'more Ylux Pendant Light has an adjustable aluminum lamp head that can be tilted by 135 degrees. The lamp head has a diameter of 9 cm and is offered in the colours aluminum polished, glossy white, matt white, glossy black or matt black. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated. The beam angle of the lamp head can be adjusted from 50 to 100 degrees by turning the glass lens out of or back into the lamp head. With a larger beam angle, the light is distributed over a larger area.

The Ylux Pendant Light Y-BPL has a textile cable that can be shortened if necessary. The cable is offered in the colours black, white or red. The cable is available in other colours on request. The canopy with a diameter of 15 cm is offered in the colours concrete grey or concrete white. Due to the natural composition of the material, the colours of the canopy may vary, i.e. lighter/darker. On request, the canopy is also available in black.

The Ylux pendant lamp is offered dimmable on site with a trailing edge phase dimmer or with an integrated rotary dimmer on the lamp head. The lamp is also available DALI dimmable on request. The Ylux pendant lamp is also offered on request as a recessed lamp with a mounting plate with a diameter of 10 cm.

### **Technical details**

Country of Manufacture

Manufacturer

Designer

protection

IP43

Scope of delivery

LED

Germany

Iess'n'more

IP43

voltage suitability 230 - 240 Volt

material aluminum, concrete, glass, Textile

beam angle50 - 100 degreesheight adjustmentheight determinable

Wattage 12.6 W
LED inclusive
Colour Rendering Index 95
Luminous flux in Im 1,200
canopy dimensions 15 cm
light head dimensions 9 cm
bulb exchange on site itself

LED number 1
light distribution directly
total height 316 cm