



# Mawa

## Wittenberg 4.0 ceiling lamp semi-flush LED

### Oberfläche

- black
- white

### Technical details

Country of Manufacture	 Germany
Manufacturer	Mawa
Designer	Jan Dinnebier
Designer 2	mawa engineering
protection	IP20
Scope of delivery	LED
voltage suitability	230 - 240 Volt
material	aluminum, metal
beam angle	38 degrees
dimming	dimmable with a trailing edge dimmer and with a leading edge dimmer
Wattage	12.7 W
LED	inclusive
Colour Rendering Index	95
Luminous flux in lm	1,100
Color temperature in Kelvin	2,700 extra warm white
light head dimensions	8 cm
bulb exchange	on site itself
light distribution	directly
Dimensions	H 9 cm   B 10 cm   L 10 cm

### Description

The Mawa Wittenberg 4.0 ceiling lamp semi-flush LED has an adjustable spotlight head. This lamp head is integrated semi-flush into the rectangular ceiling housing. It can be rotated 365 degrees and swivelled 90 degrees. The large light-emitting surface of the spotlight head is well glare-free. Neither screws nor cables are visible in the compact design of the lamp. This ceiling light is available with powder-coated white matt or black matt surfaces. On request, the lamp is also offered on request with a black ceiling housing and a lamp head in chrome, brass or copper.

The integrated LED has a colour temperature of 2,700 Kelvin extra warm white, on request it is also available with 3,000 Kelvin warm white or 4,000 Kelvin white. The Wittenberg 4.0 ceiling lamp semi-flush LED can be dimmed on site with a leading or trailing edge phase dimmer, on request it is also offered as a DALI dimmable version.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.