



# Mawa

## Bullauge 6 pendant mounting with upright

### Durchmesser in cm

- 45
- 60
- 80
- 120

### Technical details

|                                     |   |
|-------------------------------------|---|
| <b>Country of Manufacture</b>       |  Germany |
| <b>Manufacturer</b>                 | Mawa  |
| <b>Designer</b>                     | Martin Wallroth   |
| <b>surface</b>                      | weiß matt / white matt  |
| <b>Protection class / IP rating</b> | IP20  |
| <b>Contents of the package</b>      | LED   |
| <b>voltage suitability</b>          | 230 - 240 Volt  |
| <b>material</b>                     | acrylic glass, aluminum   |
| <b>cable length</b>                 | 250 cm  |
| <b>Height adjustment</b>            | height determinable   |
| <b>dimming</b>                      | dimmable with a trailing edge dimmer and with a leading edge dimmer                         |
| <b>LED</b>                          | inclusive   |
| <b>light distribution</b>           | directly and indirectly   |
| <b>Dimensions</b>                   | H 10 cm   |

### Description

The Mawa Bullauge 6 pendant mounting with upright emits light both upwards and downwards. The pendant light is available with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. As standard, the lamp is made of aluminum in powder-coated white matt. On request it can also be supplied in other RAL colours. The even distribution of the LEDs and the opaque, satinised plexiglass diffuser ensure a very homogeneous, luminous surface at the bottom of the lamp. The three smaller versions of Bullauge 6 pendant mounting with upright are suspended on three parallel cables, the largest lamp on four parallel cables. The cables have a maximum length of 250 cm and can be shortened if necessary. On request, the lamp is also available with other cable lengths or without upright.

The Bullauge 6 can be dimmed with a leading edge or trailing edge phase dimmer. On request, it is also available DALI dimmable. It is also offered with a different diameter up to 120 cm on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white.