


less'n'more

Zeus Wall / Ceiling Light Z-BDL1



Dimmbarkeit

- Push button dimmer at the canopy
- on site dimmable with a trailing edge dimmer


Oberfläche

- aluminum
- black
- white

flexible_arm

- textile white
- textile black
- textile blue
- textile anthracite
- aluminum
- textile green
- textile red
- textile brown

Technical details

Country of Manufacture	 Germany
Manufacturer	less'n'more
Designer	less'n'more
Protection class / IP rating	IP43
Contents of the package	LED
voltage suitability	230 - 240 Volt
material	aluminum, glass
beam angle	15 - 75 degrees
Wattage	4.2 W
LED	inclusive
Colour Rendering Index	90
Luminous flux in lm	450
Color temperature in Kelvin	2,700 extra warm white
canopy dimensions	7 cm
light head dimensions	3 cm
bulb exchange	on site itself
Dimensions	L max. 30 cm

Description

The Less'n'more Zeus Wall / Ceiling Light Z-BDL1 can be mounted on the wall or ceiling. It is built onto the surface. Its canopy / wall mounting made of aluminum has a diameter of 6.5 cm. This lamp has a flexible lamp arm that can be stretched and bent as desired. At maximum extension of the lamp arm, the lamp has a length of 30 cm. The flexible lamp arm is offered in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated in the lamp head.

The lamp head and the canopy are available in the surfaces aluminum and black. The Zeus Wall / Ceiling Light Z-BDL1 is offered on site dimmable with a trailing edge phase dimmer or with an integrated push button dimmer on the canopy. The version with push button dimmer can be switched and dimmed via the push button. The beam angle of the light can be continuously adjusted between 15 and 75 degrees. To do this, the glass lens is turned out of or into the lamp head. With a larger beam angle, the light is distributed over a larger area.

On request, this Zeus wall and ceiling lamp is also available with other colours for the flexible lamp arm or with a supply cable and safety plug for operation at a power socket. A larger lamp with a maximum length of 62 cm is also offered from the series. A canopy mounting plate is offered as an accessory, with which the lamp can be mounted over a flush-mounted box.