

Mawa

Seventies mounted spotlight Downlight LED dimmable

Oberfläche

- black
- white

Farbtemperatur in Kelvin

- 2,700 extra warm white
- 3,000 warm white

Technical details

Country of Germany

ManufacturerMawaDesignerJan BlieskeDesigner 2Jan Dinnebier

Year of design 2020
protection IP20
Scope of delivery LED

voltage suitability 230 - 240 Volt

Diameter in cm 9

materialaluminumbeam angle30 degrees

dimming on site dimmable with a trailing edge

dimmer

Wattage 25 W
LED inclusive
Colour Rendering Index >90

Dimensions H 18 cm | Ø 9 cm

Description

The Mawa Seventies mounted spotlight Downlight LED emits its light directly and bundled downwards. The ceiling light has a height of 18.4 cm and a diameter of 9 cm. Thanks to its compact design, there are no visible screws. The lamp is offered in the powder-coated surfaces white or black matt. On request, it is also available in other RAL colours.

The Seventies mounted spotlight Downlight LED is offered with a colour temperature of 2,700 Kelvin extra warm white or 3,000 Kelvin warm white. On request, it is also available with 4,000 Kelvin white. This light can be dimmed on site with a trailing edge phase dimmer. A DALI dimmable version is also available on request. The lamp's colour rendering index is Ra >90, but it is also available with Ra >95 on request, which is closer to natural light (Ra 100).

The Seventies mounted spotlight Downlight LED has a beam angle of 30 degrees as standard. With a larger beam angle, the light is distributed over a larger area. Optionally, the cylindrical ceiling lamp can also be ordered with a beam angle of 16 or 22 degrees in the field Order Comment.