



# Kyno Spot Duo Surface-mounted

### Oberfläche

- matt aluminum
- polished aluminum
- black
- bronze
- white

#### Elemente

- white
- gold
- aluminum polished
- black
- chrome

## Dimmbarkeit

- DALI dimmable
- on site dimmable with a trailing edge dimmer
- with Casambi module

# Description

The spotlight LDM Kyno Spot Duo Surface-mounted is made of aluminum. A frosted optical lens in each lamp head focuses the light. By turning the glass lens out of or into the lamp heads, the beam angle of the light can be continuously adjusted between 20 and 60 degrees. With a larger beam angle, the light is distributed over a larger area.

The Kyno Spot Duo Surface-mounted is available in the surfaces aluminum polished, aluminum matt, bronze, white and black matt. The lamp is offered with a ring-shaped design element on the lamp heads in aluminum polished, matt chrome, gold, white and black matt. The swivel joints are always in the same finish as the design element. Only the lamp with the element in aluminum polished has chrome swivel joints. Without the lenses turned out, the lamp heads are 18 cm long in total.

The Kyno surface-mounted ceiling spotlight is available with three dimming options: on site dimmable with a trailing edge phase dimmer, DALI dimmable or with an integrated Casambi module. The Kyno Spot Duo Surface-mounted is supplied with a colour temperature of 2,700 Kelvin extra warm white. On request, the spotlight is also available with 3,000 Kelvin warm white, 4,000 Kelvin white or with dim-to-warm technology. With the dim-to-warm function, the light colour of the LED changes to a warmer tone when dimmed (from 3,000 Kelvin warm white to 1,800 Kelvin extra warm white). The lamp is operated with Full Spectrum LEDs whose light resembles sunlight.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@wawawu.de

**Technical details** 

Country of Manufacture	🦲 Germany
Manufacturer	LDM
protection	IP20
Scope of delivery	LED
voltage suitability	230 - 240 Volt
material	aluminum
beam angle	20 - 60 degrees
Colour Rendering Index	>97
Luminous flux in lm	2,504
Color temperature in Kelvin	2,700 extra warm white
canopy dimensions	Length 50 cm, width 7 cm, height 3 cm
light head dimensions	Length 18 cm, 4 cm
bulb exchange	at the manufacturer / at the factory
system performance	2 x 12 Watt