


Deckenleuchten | 220-240 V | topLED 30 W 700 mA | CRI 90  
8138



Technische Daten	
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Optik	General Lighting
Lampenleistung	30 W
Lichtstrom (Lichtquelle)	3929 lm
Ähnlichste Farbtemperatur / Tonalität	3000 K
Farbwiedergabeindex	90 Ra
AC/DC	AC
Isolierklasse	1
IP	IP40
Glühdrahtprüfung	650°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
ETL	Nein
Fire Rated (BS 476 PT21 compliant)	Nein
Einschließlich Driver	Driver
Induction	Nein
Notbeleuchtung	Nein
Motion sensor	Nein
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Nein
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	3.950 Kg

Oberfläche Diffusor	
Material	PE
Farbe	neutral

Deckenleuchten | 220-240 V | topLED 30 W 700 mA | CRI 90  
**8138**

Double emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 156 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3929 lm, with a 131.0 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The diffuser is made of pe; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 3.950 kg.




The total absorbed power is 30 W.

The device features protection class I and can be ceiling-mounted.

Illuminotechnical Eigenschaften	
Lichtstrom (Lichtquelle)	3929 lm
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Life / Failure Ratio	
L80 B20 C0 80000h	

Mr.Magoo\_S | Ceiling Lights | Accessories

8138

 	<p>Dimmer</p> <p>PUSH DIM, 220-240V</p>	<p>Code</p> <p><u>KIT0026</u></p>
	<p>Dimmer</p> <p>Bluetooth, 85-240V</p>	<p>Code</p> <p><u>KIT0080</u></p>