

Byok

Piani Mono 165 Downlight




Oberfläche

- Aluminio pulido
- aluminio mate
- negro mate

Leuchte

- ajustable en altura
- altura ajustable

Technical details

País de origen	 Alemania
Fabricante	Byok
Diseñador	Kai Byok
Índice de protección / Protección IP	IP20
Contenido del paquete	LED
material	aluminio
longitud del cable	300 cm
Atenuación	Regulable en el sitio con control de fase inversa
LED	incluyendo
Índice de reproducción cromática	>90
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
reemplazo de la bombilla:	en el fabricante / en la fabrica
El rendimiento del sistema	10 x 3,6 Watt
Flujo total luminoso en lm	3.060
Dimensions	H 1 cm B 5 cm L 165 cm

Descripción

The Byok Piani Mono 165 Downlight is a pendant lamp. The lamp body of the Piani Mono 165 Downlight is milled out of massive aluminum and polished or eloxated by hand afterwards. Ten LEDs are dazzle-free installed due to reflector technics and they may be exchanged singly.

Three surfaces are on offer: aluminum matt, aluminum polished or black matt. This pendant lamp is offered height-determinable (the cables can be set to the desired length during assembly) or height-adjustable (the total height can also be adjusted after assembly). The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.