

Byok

Piani Quadro 48 Downlight

Oberfläche

- Aluminio pulido
- aluminio mate
- negro mate



Technical details

País de origen	 Alemania
Fabricante	Byok
Diseñador	Kai Byok
Índice de protección / Protección IP	IP20
Contenido del paquete	LED
material	aluminio
longitud del cable	250 cm
Ajuste de altura	altura determinada
Atenuación	Regulable en el sitio con control de fase inversa
LED	incluyendo
LED (reemplazable)	sí
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
El rendimiento del sistema	8 x 3,6 Watt
Flujo total luminoso en lm	2.450
distribución de la luz	directamente
Dimensions	H 0,8 cm B 48 cm L 48 cm

Descripción

The Byok Piani Quadro 48 Downlight is a pendant lamp. The strip geometry being 8 mm thin is milled out of massive aluminium and polished by hand afterwards. The reflective surface is only broken by four fine ropes out of copper braid providing for the power supply. The canopy has a diameter of 26 cm and a height of 6.8 cm. The Piani Quadro 48 Downlight runs by eight LEDs being dazzle-free installed due to the reflector technics used and which may be exchanged singly.

The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.