




Mawa

Wittenberg 4.0 ceiling lamp oval LED

Oberfläche

- negro
- blanco

Technical details

País de origen	 Alemania
Fabricante	Mawa
Diseñador	Jan Dinnebier
Diseñador 2	mawa engineering
Índice de protección / Protección IP	IP20
Contenido del paquete entrada de tensión	LED
material	230 - 240 Volt
angulo del rayo	aluminio, metal
Atenuación	38 grados
Potencia en vatios	dimnable con control de fase inversa y con reguladores de control de fase
LED	12,7 W
Indice de reproduccion cromatica	incluyendo
El flujo luminoso en lm	95
Temperatura de color en grados Kelvin	1.100
cabeza del alumbrado masa	2.700 extra blanco cálido
reemplazo de la bombilla:	8 cm
distribución de la luz	en el sitio mismo
Dimensions	directamente
	H 10 cm B 8 cm L 18 cm

Descripción

The Mawa Wittenberg 4.0 ceiling light oval LED has an adjustable spotlight head. The head can be rotated 365 degrees and swivelled 90 degrees. The design is reduced so that neither screws nor cables are visible. The lamp head has a large light-emitting surface that is well glare-free. The Wittenberg 4.0 ceiling light oval LED is available in black and white. The integrated LED has a colour temperature of 2,700 Kelvin extra warm white. On request it is also supplied with 3,000 Kelvin warm white or 4,000 Kelvin white. The light can be dimmed on site with a leading edge or trailing edge phase dimmer. On request, it is also available as a DALI dimmable version.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.