


Mawa

Wittenberg 4.0 Druff table lamp LED

Oberfläche

- negro
- beige
- azul
- gris
- rojo
- blanco

Technical details

País de origen	 Alemania
Fabricante	Mawa
Diseñador	Jan Dinnebier
Diseñador 2	Martin Wallroth
Índice de protección / Protección IP	IP20
Contenido del paquete	LED
entrada de tensión	230 - 240 Volt
material	aluminio, metal
angulo del rayo	38 grados
Color del cable	gris
longitud del cable	250 cm
Atenuación	integrada Dimmer pulsador
LED	incluyendo
Indice de reproduccion cromatica	95
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
cabeza del alumbrado masa	8 cm
reemplazo de la bombilla:	en el sitio mismo
El rendimiento del sistema	2 x 12,7 Watt
Flujo total luminoso en lm	2.200
distribución de la luz	directamente
Dimensions	H 9 cm B 10 cm L 20 cm

Descripción

The Mawa Wittenberg 4.0 Druff table lamp LED has two individually adjustable spotlight heads. Each lamp head can be individually rotated by 365 degrees and swivelled by 90 degrees. The lamp heads are both half-flush mounted in the lamp housing. The lamp is dimmed continuously by a push button dimmer on the housing. A memory function saves the last light intensity setting and automatically selects it again when the lamp is switched on again.

The Wittenberg 4.0 Druff table lamp LED is available in powder-coated matt black, beige, grey, blue, red or matt white. On request it is also available with a black housing and lamp heads in copper or completely in other RAL colours. As standard, the lamp is supplied with a colour temperature of 2,700 Kelvin extra warm white. On request it is also available with 3,000 Kelvin warm white or 4,000 Kelvin white. The colour rendering index of the lamp is Ra > 95, which is closer to natural light (Ra 100). The scope of delivery includes a honeycomb grid with which the light can be emitted without glare.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.