




Catellani & Smith

Syphaduepassi Set 9

Technical details

| | |
|---|--|
| País de origen |  Italia |
| Fabricante | Catellani & Smith |
| Diseñador | Enzo Catellani |
| año | 2018 |
| Índice de protección / Protección IP | IP20 |
| Contenido del paquete entrada de tensión | LED 230 - 240 Volt |
| material | latón, vidrio |
| Atenuación | Regulable en el sitio con control de fase inversa |
| Base / Portalámparas | G4 |
| LED | incluyendo |
| Índice de reproducción cromática | 80 |
| Temperatura de color en grados Kelvin | 2.700 extra blanco cálido |
| reemplazo de la bombilla: | en el sitio mismo |
| El rendimiento del sistema | 9 x 1 Watt |
| Flujo total luminoso en lm | 675 |
| Dimensions | H 4 x 45 + 5 x 75 cm |

Descripción

The Catellani & Smith Syphaduepassi Set 9 consists of nine complete outdoor floor lamps, ready for connection, with all necessary accessories. The nine lamps can be easily linked and connected together using the Catellani & Smith Quick Connectors system. Only a single power connection is required for installation. The driver included in the scope of supply is suitable for a maximum of 30 W and can be dimmed on site. It has a connection cable for the power connection. All necessary plug connections are included. The set comprises the following:

- Four lamps with a height of 45 cm
- five lamps with a height of 75 cm
- an extension cable with a length of 500 cm
- a driver necessary for lamp operation.

The Syphaduepassi outdoor floor lamps can be fixed with their ground spike up to 25 cm into the ground. The height specifications of the lamps (45 cm and 75 cm) are indicated without ground spike. The light emitted is focused and glare-free by the lamps glass lens. The brass lamp rods are bendable and can be realigned if necessary.

With IP44 protection, the Syphaduepassi lamps are protected against splashing water on all sides and solid foreign bodies with a diameter of 1 mm or more. With IP65 protection, the lamp rods are dust-tight and protected against strong jets of water from any angle. Drivers and extension cables are protected against temporary immersion with IP67 protection. Other sets with two, three, four or five complete lamps are available for Syphaduepassi lamps. A complete single lamp with a height of 45 cm or 75 cm is also offered.