



less'n'more

Athene Wall Light A-BWL2

Dimmbarkeit

- Dimmer táctil en el soporte de pared
- Regulable en el sitio con control de fase inversa


Oberfläche

- aluminio
- negro
- blanco

flexible_arm

- azul textil
- antracita textil
- aluminio
- verde textil
- rojo textil
- marrón textil
- blanco textil
- negro textil

Technical details

País de origen	 Alemania
Fabricante	less'n'more
Diseñador	less'n'more
Índice de protección / Protección IP	IP43
Contenido del paquete	LED
entrada de tensión	230 - 240 Volt
material	aluminio, vidrio
angulo del rayo	25 - 100 grados
Potencia en vatios	4,8 W
LED	incluyendo
Indice de reproduccion cromatica	90
El flujo luminoso en lm	600
Temperatura de color en grados Kelvin	2.700 extra blanco cálido
cabeza del alumbrado masa	7 cm
reemplazo de la bombilla:	en el sitio mismo
Montaje en pared Dimensiones	8 cm
Dimensions	H max. 63 cm

Descripción

The Less'n'more Athene Wall Light A-BWL2 is mounted on the wall as standard. It is also suitable for mounting on a flush-mounted box. Its mounting plate or wall bracket has a diameter of 8 cm and can be freely mounted 360 degrees during installation. This Athene wall lamp has a flexible lamp arm that can be stretched and bent as desired. With a maximum extension of the lamp arm, the lamp has a height of 63 cm. The flexible arm is available in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

The lamp head and wall bracket are offered in the surfaces aluminum and black. By turning the glass lens out of or into the lamp head, the beam angle of the light can be continuously adjusted between 25 and 100 degrees. With a larger beam angle, the light is distributed over a larger area. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated as the light source.

The Athene Wall Light A-BWL2 is available on site dimmable with a trailing edge phase dimmer or with a built-in push button dimmer on the wall bracket. The version with push button dimmer can be switched and dimmed via the push button. The flexible lamp arm is offered in additional special colours on request. In addition, the lamp is also available on request with a supply cable and safety plug for direct connection to a power supply.