

Knapstein


LISA-60



Oberfläche

- níquel
- negro
- bronce

Technical details

País de origen	 Alemania
Fabricante	Knapstein
Diseñador	Knapstein
año	2021
Índice de protección / Protección IP	IP20
Contenido del paquete	LED
entrada de tensión	230 - 240 Volt
Diámetro en cm	60
material	latón
Ajuste de altura	altura ajustable
Atenuación	control por movimientos
Potencia en vatios	72 W
LED	incluyendo
Índice de reproducción cromática	>90
El flujo luminoso en lm	7.850
Temperatura de color en grados Kelvin	2200 - 3000 ajustable
Dimensiones del dosel	35 cm
reemplazo de la bombilla:	en el fabricante / en la fabrica
altura total	70 - 170 cm
Dimensions	H 2,8 cm Ø 60 cm

Descripción

The Knapstein LISA-60 is a ring-shaped pendant lamp with a diameter of 60 cm. The ring-shaped lamp body is 2.8 cm high and 1.8 cm wide. By pulling or lifting the lamp, the total height of the lamp can be adjusted continuously between 70 cm and 170 cm. The lamp can also be suspended from a sloping ceiling. The light from this pendant light is emitted upwards and downwards at the same time. The uplight and the downlight can be switched separately and dimmed continuously via gesture control. Using gesture control, it is also possible to adjust the light colour for the uplight and downlight to a warmer tone (between the colour temperature of 3,000 Kelvin warm white and 2,200 Kelvin extra warm white). All dimming and light colour settings are saved via a memory function and automatically reset the next time the lamp is switched on.

A wiping hand movement in the sensor area switches the light on or off. To dim the light, the hand is held in the sensor area for a longer period of time. The lamp flickers briefly after the dimming process is completed. The desired light colour can then be set by again holding the hand in the sensor area for a longer period of time. The LISA-60 is available in matt nickel, black and bronze effect finishes. On request, the LISA is also available in other sizes or finishes. Its ceiling canopy has no visible screws as it is held in place by magnets.