

Lichtlauf

UpLight Down

Durchmesser in cm


- 50
- 40
- 30

Kabelfarbe

- rojo
- blanco
- gris



Technical details

País de origen	 Alemania
Fabricante	Lichtlauf
Diseñador	Christoph Matthias
año	2012
Índice de protección / Protección IP	IP20
Contenido del paquete	Leuchtmittel/ Bulb
entrada de tensión	110 - 240 Volt
material	polietileno, Textil
superficie	blanco
longitud del cable	250 cm
Atenuación	Regulable en el sitio
Base / Portalámparas	E27
conectividad	en la delantera
Alimentación (máx. Watt)	70 Watt
reemplazo de la bombilla:	en el sitio mismo

Descripción

The UpLight Down light run is the floor version of the UpLight lamp. Supplemented with a stand ring and foot switch, this lamp illuminates low room zones with its mild light, creating a special and variable lighting mood. The white hollow sphere made of resistant and high-quality polyethylene is available in three different diameters, the textile cable in three different colours. The UpLight Down by Lichtlauf has an E27 ceramic socket and can be operated with conventional halogen bulbs as well as with LED retrofit bulbs. This portable lamp is available with a diameter of 30 cm, 40 cm or 50 cm. The textile 2.5 m cable is optionally available in white, red or grey. On request, the textile cable is also available in other colours and lengths.