



LED



## bullauge 6 SYSTEMLEUCHTE bu6-450-G5

Die Wand-, Decken- und Pendelleuchte bu6 (LED) ist jetzt in der fünften Generation erhältlich. Durch die opake Plexiglasscheibe und die gleichmäßige Anordnung der LEDs entsteht eine diffuse und sehr homogene Leuchtfläche. Dank mawa-Verschluss ist eine Ein-Mann-Revision unkompliziert durchführbar. Die Pendelvarianten der bu6 mit einem Durchmesser von 450 mm haben serienmäßig eine 3-fach-Parallelabhängung inkl. einem Anschlussbaldachin (ø76 mm).

-  weiß matt (RAL 9016)
-  weitere RAL-Farben auf Anfrage





bu6-450-G5-...-wm





◀ 450 ▶

bu6-450-G5-...-wa  
bu6-450-G5-...-wa-u



◀ 450 ▶

bu6-450-G5-...-p  
bu6-450-G5-...-p-u



◀ 450 ▶

(\* Standardmaß)

### bu6-450-G5

Design: Martin Wallroth

Engineering: mawa design

Wand-, Wandabstands-, Decken- und Pendelleuchte, Aluminiumgehäuse pulverbesch., satiniertes Plexiglas 3 mm,

**LED Modul standard G5:**

**Downlight:** 54 W, Ra > 90 (typ. 92)

Lichtfarben / Lichtstrom: 2700 K / 6660 lm,  
3000 K / 6988 lm,

**Uplight:** 12 W, Ra > 90 (typ. 92)

Lichtfarben / Lichtstrom: 2700 K / 1480 lm,  
3000 K / 1552 lm,

Lebensdauer Standard-LED:

L80 > 54.000 h (IES LM-80 / TM-21)

EEL = A++-A

bu6-450-G5-3 1-10V dimmbar

bu6-450-G5-4 DALI dimmbar

bu6-450-G5-7 Phasen- und -abschnitt dim.

bu6-450-G5-8 Push

**Montagemöglichkeiten:**

**Wand- und Deckenmontage (-wm),**

Wandanschlussplatte (-wa) mit 3 Distanzen,  
optional mit Uplight (-wa-u), Standardlänge  
50 mm (andere Längen auf Anfrage),

Pendelabhängung (-p) inkl. Baldachin,

3-fach-Parallelabhängung und Zuleitung,  
optional mit Uplight (-p-u)

Gewicht: bu6-450-G5-wm 4.500 g

## Product Information

mawa®

LED



### bullauge 6 SYSTEM LIGHT bu6-450-G5

The wall, ceiling, and pendant light, bu6 (LED) is now available in its 5th generation. The opaque plexiglass pane and even arrangement of LEDs creates a diffused and very homogenous lighting surface. Thanks to the mawa-closure, maintenance of the light is easy to for one person to conduct. The pendant variation of the bu6, with a diameter of 450 mm, includes the series canopy (Ø76 mm) with three parallel suspension cables for connection.



- ☐ white matt (RAL 9016)
- ☒ other RAL colors on request





bu6-450-G5-...-wm



bu6-450-G5-...-wa  
bu6-450-G5-...-wa-u



bu6-450-G5-...-p  
bu6-450-G5-...-p-u



(\* standard size)

#### bu6-450-G5

Design: Martin Wallroth

Engineering: mawa design

Wall-mounted, wall-spaced, ceiling-mounted and pendant luminaire, Aluminium housing powder-coated, satined plexiglass 3 mm,

LED module standard: G5:

**Downlight:** 54 W, Ra > 90 (typ. 92)

Light colour / luminous flux: 2700 K / 6660 lm, 3000 K / 6988 lm,

**Uplight:** 12 W, Ra > 90 (typ. 92)

Light colour / luminous flux: 2700 K / 1480 lm, 3000 K / 1552 lm,

Life time LED standard:

L80 > 54.000 h (IES LM-80 / TM-21)

EEI = A++-A

bu6-450-G5-3 1-10V dim.

bu6-450-G5-4 DALI dim.

bu6-450-G5-7 Leading edge/trailing edge dim.

bu6-450-G5-8 Push

**Mounting possibilities:**

Wall and ceiling-mounted (-wm),

Wall connecting plate (-wa) with 3 distances, optionally available with an uplight (-wa-u), standard length 50 mm (other lengths available on request),

Pendant light (-p) incl. canopy, 3 parallel suspension cables and electrical supply optionally available with an uplight (-p-u)


Weight: bu6-450-G5-wm 4.500 g

## bullauge 6 Serie bullauge 6 series SYSTEMLEUCHTE SYSTEM LIGHT **bu6-450-G5**


**bu6-450 (G5)**




**bu6-600 (G5)**



**bu6-800 (G5)**



**bu6-900 (G4) (auf Anfrage)**



**bu6-1200 (G4)**



### Lichtverteilung Light distribution






Downlight



Uplight (bu6-450 –  
bu6-900)

### Montagemöglichkeiten Mounting possibilities



Wand- und Deckenmontage (-wm)  
Wall and ceiling-mounted (-wm)

Wandanschlussplatte (-wa)  
Wall connecting plate (-wa)

Pendelabhängung (-p)  
Pendant light (-p)



Foto: Stefan Wolf Lucks | Waldklinikum Eisenberg