


Deckenleuchten | 220-240 V | topLED 26 W | CRI 90
7595



| Technische Daten | |
|---|------------------|
| Installationsposition | Decke |
| Installationsumgebung | Indoor |
| Lichtquelle | LED |
| Optik | General Lighting |
| Light emission direction | downward |
| Lampenleistung | 26 W |
| Lichtstrom (Lichtquelle) | 3118 lm |
| Frequency | 60 - 50 Hz |
| Ähnlichste Farbtemperatur / Tonalità | 3000 K |
| Farbwiedergabeindex | 90 Ra |
| AC/DC | AC |
| Isolierklasse | 1 |
| IP | IP40 |
| Glühdrahtprüfung | 850° |
| Direkte Montage auf normal entflammaren Oberflächen | Ja |
| CE | Ja |
| ETL | Nein |
| Einschließlich Driver | Ja |
| Induzione | Nein |
| Notbeleuchtung | Nein |
| Motion sensor | Nein |
| Schwenkbarkeit | Ja |
| Drehbarkeit | Nein |
| Begehbarkeit | Nein |
| Überrollbarkeit | Nein |
| Einschließlich Kabel | Nein |
| Harzbeschichtung | Nein |

| Oberfläche Gehäuse | |
|---------------------|-------------------------|
| Material | Aluminium |
| Farbe | Weiß geprägtem RAL 9003 |
| Bearbeitungstyp | Lackierung |
| Oberfläche Diffusor | |
| Material | PC |
| Farbe | Opal |



Deckenleuchten | 220-240 V | topLED 26 W | CRI 90
7595

Single emission ceiling lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 108 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3118 lm, with a 119.9 lm/W nominal luminous efficacy and an operating lifetime (L80) of 80000 hours.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of PC. The ingress protection degree is IP40; The power supply driver is included in the delivery.

The total absorbed power is 26 W.

The device features protection class I and can be ceiling-mounted.

| Illuminotechnical Eigenschaften | |
|---------------------------------------|----------------|
| Light Output Ratio (LOR) | 75 % |
| Lichtstrom (Lichtquelle) | 3118 lm |
| Leuchten Lichtstrom | 2342 lm |
| Consumption | 31 W |
| Leuchten Lichtausbeute | 75 lm/W |
| Farbtemperatur | 3000 K |
| Standard Deviation of Colour Matching | 3 Step MacAdam |
| Farbwiedergabeindex | 90 Ra |
| Life / Failure ratio | L80C0B20 |

| UGR | |
|-------------------|----------|
| X=4H Y=8H | S=0.25H |
| Reflection factor | 70/50/20 |
| UGR transversal | < 25 |
| UGR axial | < 16 |

| OPTICAL | |
|-----------------------------|--------------|
| Light distribution simmetry | Asymmetrical |
| Ottica C0/C180 | 129° |
| Ottica C90/C270 | 111° |

