

Lichtlauf

UpLight Down




Durchmesser in cm

- 50
- 40
- 30

Kabelfarbe

- blanc
- gris
- rouge

Technical details

Pays de fabrication	 Allemagne
Fabricant	Lichtlauf
Créateur	Christoph Matthias
année	2012
Indice de protection / Indice IP	IP20
Contenu de la livraison	Leuchtmittel/ Bulb
aptitude de tension	110 - 240 Volt
matériel	polyéthylène, Textile
surface	blanc
longueur de câble	250 cm
atténuation	dimmerable sur place
Socle / Douille	E27
commutabilité	sur la conduire
Puissance (max. Watt)	70 Watt
remplacement des ampoules :	sur le site meme

Description

The UpLight Down light run is the floor version of the UpLight lamp. Supplemented with a stand ring and foot switch, this lamp illuminates low room zones with its mild light, creating a special and variable lighting mood. The white hollow sphere made of resistant and high-quality polyethylene is available in three different diameters, the textile cable in three different colours. The UpLight Down by Lichtlauf has an E27 ceramic socket and can be operated with conventional halogen bulbs as well as with LED retrofit bulbs. This portable lamp is available with a diameter of 30 cm, 40 cm or 50 cm. The textile 2.5 m cable is optionally available in white, red or grey. On request, the textile cable is also available in other colours and lengths.