



Betec

Angulus 75 cm Typ 15

Oberfläche

- chrome
- or mat
- Laiton brillant
- Laiton mat
- nickel brillant
- matte de nickel
- noir
- Browning
- or brillant

Technical details

Pays de fabrication	💻 Allemagne
fabricant	Betec
concepteur	Horst Lettenmayer
protection	IP20
Contenu de la livraison	LED
aptitude de tension	110 - 240 Volt
Projection en cm	15
matériel	laiton
Puissance en Watt	26,7 W
LED	y compris
Indice de rendu des couleurs	>90
Flux lumineux en lm	2.414,7
La température de couleur en Kelvin	2.700 extra blanc chaud
Dimensions	H 21,5 cm L 75 cm

Description

With its angular shape, the Betec Angulus fits particularly harmoniously with many picture frames. As its lamp head can be rotated around its own axis, this lamp is particularly suitable as picture, menu and music stand lighting. A Duo LED is integrated as the light source. A Duo LED consists of two LEDs in one housing and therefore has a particularly high light output. The lamp is supplied with a diffuser cover that reduces the glare of the emitted light. The Angulus is offered here with a length of 75 cm and a projection of 15 cm (bracket type 15).

The Betec Angulus 75 cm is available in the surfaces brass glossy, brass matt, chrome, nickel glossy, nickel matt, burnished, black matt, gold glossy and gold matt. The scope of delivery includes a mounting set with which the lamp can be easily attached directly to a picture or to the wall. The picture light has a colour temperature of 2,700 Kelvin extra warm white. On request, it is also available with 2,400 Kelvin extra warm white, 3,000 Kelvin warm white or 3,100 Kelvin white. The integrated LED is characterised by very good colour rendering with a high colour rendering index of Ra >90. A touch dimmer is offered as an accessory, with which the lamp can be switched and dimmed by touch. The manufacturer Betec also offers the Angulus picture light in three other lengths and with a projection of 20 cm or 25 cm.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@wawawu.de

www.wawawu.eu