

Mawa

Wittenberg 4.0 Druff table lamp LED

Oberfläche

- zwart
- beige
- blauw
- grijs
- rood
- wit

Technical details

Land van fabricage

fabrikant

ontwerper 2

bescherming

Omvang van de levering

voltage geschiktheid

. . .

materiaal

stralingshoek

kabel kleur kabellengte

Kabelleligte

dimmen

LED Kleurweergave-index

Kleurtemperatuur in Kelvin

lampkop massa

bulb vervangen:

prestaties van het systeem

Totale lichtstroom in Im

lichtverdeling

Dimensions

Duitsland

Mawa

Jan Dinnebier

Martin Wallroth

IP20

LED

230 - 240 Volt

aluminium, metaal

38 Graad

grijs

250 cm

geïntegreerde Drukknop dimmer

inclusief

95

2.700 extra warm wit

8 cm

ter plaatse zelf

2 x 12,7 Watt

2.200

direct

H 9 cm | B 10 cm | L 20 cm

Omschrijving

The Mawa Wittenberg 4.0 Druff table lamp LED has two individually adjustable spotlight heads. Each lamp head can be individually rotated by 365 degrees and swivelled by 90 degrees. The lamp heads are both half-flush mounted in the lamp housing. The lamp is dimmed continuously by a push button dimmer on the housing. A memory function saves the last light intensity setting and automatically selects it again when the lamp is switched on again.

The Wittenberg 4.0 Druff table lamp LED is available in powder-coated matt black, beige, grey, blue, red or matt white. On request it is also available with a black housing and lamp heads in copper or completely in other RAL colours. As standard, the lamp is supplied with a colour temperature of 2,700 Kelvin extra warm white. On request it is also available with 3,000 Kelvin warm white or 4,000 Kelvin white. The colour rendering index of the lamp is Ra > 95, which is closer to natural light (Ra 100). The scope of delivery includes a honeycomb grid with which the light can be emitted without glare.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.