



Knapstein JILL-s

Technical details

Kn
Kna
IP2
LED
230
me
geb
inc
>9(
2.7
len
2 x
2.8
H 1

Duitsland Knapstein Knapstein IP20 LED 230 - 240 Volt messing gebarencontrole inclusief >90 2.700 extra warm wit lengte 22, breedte 22 cm 2 x 21 Watt 2.800 H 160 cm | B 1,6 cm

Omschrijving

The Knapstein JILL-S floor lamp has a rotating and swivelling lamp rod which can be reoriented again and again via a joint on the lamp base. The floor lamp emits both direct light to the front and indirect light to the wall. The two light sources of the lamp can be switched and dimmed separately by gesture control. The sensor for gesture control is located respectively in the centre of the lamp pole. The corresponding light source is switched on or off with a wiping hand movement in the sensor area. To dim the light, the hand is held in front of the respective sensor until the desired light intensity is reached. A memory function saves the last selected light intensity and sets it automatically the next time the light is switched on. In the event of a mains failure, the light is automatically switched on if it was previously on. It remains switched off if it was also switched off before the power failure. This function is suitable for use with switchable sockets.

Two LEDs each with a colour temperature of 2,700 Kelvin extra warm white are integrated as light sources. The JILL-S from Knapstein has a matt nickel-plated surface and is 160 cm high.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@wawawu.de

www.wawawu.eu