



# less'n'more Zeus Wall Light Z-BWL2

## Dimmbarkeit

- Touch Dimmer op de wandhouder
- dimbaar op locatie met faseafsnijding dimmer

#### Oberfläche

- aluminium
- zwart
- wit

## flexible\_arm

- textiel antraciet
- aluminium
- textile groen
- textiel rood
- textiel bruine
- textiel wit
- textiel zwart
- textiel blau

# Omschrijving

The Less'n'more Zeus Wall Light Z-BWL2 is a surface-mounted lamp for the wall. It is also suitable for mounting on a flush-mounted box. Its wall mounting / mounting plate is made of aluminum and has a diameter of 10 cm. When mounting, the wall mounting can be freely mounted by 360 degrees. The wall lamp has a flexible lamp arm that can be stretched and bent as desired. At maximum extension of the arm, the lamp has a height of 61 cm. The flexible arm is available in the following colours: aluminum, textile black, white, anthracite, blue, green, red and brown.

Lamp head and wall bracket are offered in the surfaces aluminum and black. The beam angle of the light can be adjusted continuously between 15 and 75 degrees by turning the glass lens out of or into the lamp head. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated as illuminant.

The Zeus Wall Light Z-BWL2 is available dimmable on site with a trailing edge phase dimmer or with a built-in push button dimmer on the wall bracket. The version with push button dimmer can be switched and dimmed via the push button. The flexible lamp arm is offered in special colours on request. This Zeus wall lamp is also available on request with a supply cable and safety plug for direct connection to a power supply. In addition to this lamp, Less'n'more also offers the smaller Zeus Wall Light Z-BWL1 with a maximum height of 30 cm.

K-Meral GmbH & Co. KG | Sachsenweg 9 | Hambau / Öko-Zentrum NRW / Halle 4 | 59073 Hamm Tel.: +49 (0) 2381 - 905 9350 | Fax: +49 (0) 2381 - 905 9310 | info@wawawu.de

**Technical details** 

Land van fabricage
fabrikant
ontwerper
bescherming
Omvang van de levering
voltage geschiktheid
materiaal
stralingshoek
Wattage
LED
Kleurweergave-index
Lichtstroom in lm
Kleurtemperatuur in Kelvin
lampkop massa
bulb vervangen:
Wall mount Afmetingen
Dimensions

less'n'more less'n'more IP43 LED 230 - 240 Volt aluminium, glas 15 - 75 Graad 4,2 W inclusief 90 450 2.700 extra warm wit 3 cm ter plaatse zelf 10 cm H max. 61 cm

💻 Duitsland