



Lichtlauf

UpLight Down

Durchmesser in cm

- 50
- 40
- 30

Kabelfarbe

- grijs
- rood
- wit

Technical details

Land van herkomst	 Duitsland
Fabrikant	Lichtlauf
Ontwerper	Christoph Matthias
jaar	2012
Beschermingsklasse / IP-bescherming	IP20
Leveringsomvang	Leuchtmittel/ Bulb
voltage geschiktheid	110 - 240 Volt
materiaal	polyethyleen, textiel
oppervlak	wit
kabellengte	250 cm
dimmen	dimbaar op locatie
Voet / fitting	E27
schakelbaarheid	aan de lijn
Vermogen (max. Watt)	70 Watt
bulb vervangen:	ter plaatse zelf

Omschrijving

The UpLight Down light run is the floor version of the UpLight lamp. Supplemented with its stand ring and foot switch, this lamp illuminates low room zones with its mild light, creating a special and variable lighting mood. The white hollow sphere made of resistant and high-quality polyethylene is available in three different diameters, the textile cable in three different colours. The UpLight Down by Lichtlauf has an E27 ceramic socket and can be operated with conventional halogen bulbs as well as with LED retrofit bulbs. This portable lamp is available with a diameter of 30 cm, 40 cm or 50 cm. The textile 2.5 m cable is optionally available in white, red or grey. On request, the textile cable is also available in other colours and lengths.