

Byok

Piani Quadro 48 Downlight

Oberfläche

- Aluminium polerowane
- Matt aluminium
- czarny matowy



Technical details

Kraj produkcji	 Niemcy
Producent	Byok
Projektant	Kai Byok
Stopień ochrony / Stopień ochrony IP	IP20
Zawartość opakowania	LED
napięcie przydatność	230 - 240 Volt
tworzywo	aluminium
długość kabla	250 cm
Regulacja wysokości	wysokość ustalona
ściemnianie	ściemniająca kontrola faz przyciemniania
LED	łącznie
LED (wymienny)	tak
Temperatura barwowa w stopniach Kelvina	2.700 extra biała ciepła
wydajność systemu	8 x 3,6 Watt
Całkowity strumień świetlny w lm	2.450
dystrybucja światła	bezpośrednio
Dimensions	H 0,8 cm B 48 cm L 48 cm

Opis

The Byok Piani Quadro 48 Downlight is a pendant lamp. The strip geometry being 8 mm thin is milled out of massive aluminium and polished by hand afterwards. The reflective surface is only broken by four fine ropes out of copper braid providing for the power supply. The canopy has a diameter of 26 cm and a height of 6.8 cm. The Piani Quadro 48 Downlight runs by eight LEDs being dazzle-free installed due to the reflector technics used and which may be exchanged singly.

The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.