

Mawa


Bullauge 6 wall mounting



Durchmesser in cm

- 45
- 60
- 80
- 120

Technical details

| | |
|---|--|
| Kraj produkcji |  Niemcy |
| Producent | Mawa |
| Projektant | Martin Wallroth |
| powierzchnia | weiß matt / white matt |
| Stopień ochrony / Stopień ochrony IP | IP20 |
| Zawartość opakowania | LED |
| napięcie przydatność | 230 - 240 Volt |
| tworzywo | aluminium, szkło akrylowe |
| ściemnianie | ściemnialne z przecinaniem fazy i ściemniaczem z regulacją fazy |
| LED | łącznie |
| dystrybucja światła | bezpośrednio |
| Dimensions | H 10 cm |

Opis

The Mawa Bullauge 6 wall mounting is installed directly on the wall or ceiling. The lamp is available in four sizes: with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. The housing is made of aluminum and is powder-coated white matt. The opaque, satin diffuser made of plexiglass and the evenly distributed LEDs provide a diffuse and very homogeneous lighting surface. The patented closure of the wall and ceiling lamp allows easy mounting.

The Bullauge 6 is dimmable on site with a leading edge or trailing edge phase dimmer. DALI, 1-10 Volt or push dimmable versions are also available on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white. Other diameters up to 120 cm or other RAL colours are also offered on request. In addition to this lamp for direct wall or ceiling mounting, a lamp with wall or ceiling distance mounting is also available.