




Mawa

Bullauge 6 pendant mounting

Durchmesser in cm

- 45
- 60
- 80
- 120

Technical details

Kraj produkcji	 Niemcy
Producent	Mawa
Projektant	Martin Wallroth
powierzchnia	weiß matt / white matt
Stopień ochrony / Stopień ochrony IP	IP20
Zawartość opakowania	LED
napięcie przydatność	230 - 240 Volt
tworzywo	aluminium, szkło akrylowe
długość kabla	250 cm
Regulacja wysokości	wysokość ustalona
ściemnianie	ściemnialne z przecinaniem fazy i ściemniaczem z regulacją fazy
LED	Łącznie
Wskaźnik oddawania barw	>90
dystrybucja światła	bezpośrednio
Dimensions	H 10 cm

Opis

The Mawa Bullauge 6 pendant mounting emits its light directly downwards. This pendant lamp is offered with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. The lamp is supplied as standard in powder-coated white matt aluminum. The even distribution of the LEDs and the opaque, satin diffuser made of plexiglass creates a diffuse and very homogeneous lighting surface. The Bullauge 6 pendant mounting is suspended for the three smaller versions on three parallel cables with a maximum length of 250 cm, the largest lamp with a diameter of 120 cm is suspended on four parallel cables. Other cable lengths are available on request. In addition to this pendant lamp with direct light output, one with additional uplight is also offered.

The Bullauge 6 can be regulated with a leading edge or trailing edge phase dimmer. DALI, Push or 1-10 Volt dimmable lamps are also available on request. In addition, other diameters up to 120 cm and other RAL colours are offered for the lamp on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white.